

Si-10

Part number
SI10UL02UN23

Integrated detection unit for installation in tight spaces.

- ⊕ Mounting bracket
- ⊕ Integrated detection unit
- ⊕ Compact monobloc design



Technical details

Max flow rate	5 gph, 19 l/h
Max discharge head	33 ft, 10 m
Max pressure	46 ft, 14 m
Insulation class	Double insulation
Mains supply	230V: (SI10UL01UN23)
Operation conditions	70%: 3s ON - 1s OFF
Weight	0.86 lb, 0,41 kg
Master pack quantity	25
Safety switch	NC 8A resistive - 250 V
Detection	Integrated detection unit
Thermal protection	240 deg. F (auto-reset)

Pump dimensions

Detection levels

	Length	Width	Height		
Pump	2 5/8", 96 mm	1 3/4", 44 mm	3", 76 mm	ON	23/32", 18 mm
				OFF	15/32", 12 mm
Packaging	4 13/32", 170 mm	3 19/32", 160 mm	3 19/32", 95 mm	SAFETY	13/16", 21 mm

Pump sound levels

at 3,3ft or 1m according to EN ISO3744 (dBA)

Kit contents

<= 23 Si-10 piston pump, with integrated float detection unit
Anti-vibration mounting bracket
Power Cable, 5' (2 power wires, 2 safety wires)
90 Deg Rubber Elbow, 19/32" i.d. x L 2 1/3"
Vent Tube, 5/32" i.d. x L 2 15/16"

Pump technology

Mini condensate removal pump

Installation

Next to unit
Wall mounted

Application

Air conditioning

Safety standards

UL/CSA by Intertek



Source URL: <https://sauermanngroup.com/en/product/pump/si-10>