

DATA SHEET

SI-AQ PRO

The Latest in Handheld IAQ Monitoring
& Real Time Data Logging for Complete
Air Quality Analysis

Accurate / Reliable / Robust / Fast

- Up to 3 Gases
- Temp., %RH, & Barometric Pressure Included
- Real-Time Data Logging
- Active Internal Sampling Pump
- Large Internal Memory (2,000 Tests)
- Protective Magnetic Rubber Boot
- Optional Wireless Printer
- Optional Handheld Probe



Select Up To 3 Gases:
CO₂, CO, NO₂, NO, O₂, SO₂,
H₂S, Formaldehyde



Long Lasting Rechargeable
Battery & AC Charger



Light Weight & Durable



Si-AQ PC Software
& USB Cable

Parameter	Sensor	Range	Resolution	Accuracy
Relative Humidity	Capacitive	5 - 95 %	0.1 %	±2 % RH
Ambient Temperature	Pt100	-40 to 257 °F -40 to 125 °C	0.1 °F 0.1 °C	±0.4 °F (32 - 140 °F) ±0.4 °C (0 - 60 °C)
Barometric Pressure	Piezoresistive	260 - 1,260 mbar	1 mbar	±2 mbar
Differential Pressure*	Piezoresistive	-40 inH ₂ O to 40 inH ₂ O -100 mbar to 100 mbar	0.1 inH ₂ O 0.1 mbar	±1 % rdg
Temperature Type K T1	Tc K	0 - 2,000 °F 0 - 1,100 °C	1 °F 1 °C	5 °F / 3 °C or 2 % rdg
Air Velocity	Calculated	0 - 300 ft/sec 0 - 91 m/s	1 ft/sec 1 m/s	-
Electromagnetic Compatibility	EN 61326-1, Portable Equipment			

Si-AQ Pro Ordering Code

Example Part #: PRO - Si-AQ CO₂ Sensor (0 - 5000 ppm) - Si-AQ CO Cell (0 - 200 ppm) - Si-AQ H₂S Cell (0 - 200 ppm) = CO₂, CO, H₂S

Parameter	Sensor	Range	Resolution	Accuracy
Si-AQ CO₂ Sensor (0 - 5000 ppm) Carbon Dioxide (CO ₂) ¹	NDIR	0 - 5,000 ppm	1 ppm	±2 % rdg ±10 ppm
Si-AQ CO Cell (0 - 200 ppm) Carbon Monoxide (CO) ¹	EC ^{2,5}	0 - 200 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
Si-AQ CH₂O Cell (0 - 10 ppm) Formaldehyde ^{3,4}	EC ^{2,5}	0 - 10 ppm 0 - 10,000 ppb	1 ppb	±5 % rdg ±50 ppb
Si-AQ H₂S Cell (0 - 100 ppm) Hydrogen Sulfide (H ₂ S) ¹	EC ^{2,5}	0 - 100 ppm	1 ppm	±4 % rdg ±0.5 ppm
Si-AQ NO₂ Cell (0 - 20 ppm) Nitrogen Dioxide (NO ₂) ¹	EC ^{2,5}	0 - 20 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
Si-AQ O₂ Cell (0 - 25%) Oxygen (O ₂)	EC ^{2,5}	0 - 25 %	0.1 %	±0.1 % vol rdg
Si-AQ SO₂ Cell (0 - 20 ppm) Sulfur Dioxide (SO ₂) ¹	EC ^{2,5}	0 - 20 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
Si-AQ NO Cell (0 - 250 ppm) Nitric Oxide (NO) ¹	EC ^{2,5}	0 - 250 ppm	0.1 ppm	±4 % rdg ±0.5 ppm

¹ Other ranges are available upon request

² Electrochemical

³ Accuracy based on laboratory conditions

⁴ This sensor may have interference from H₂, CO, H₂S and other reducing gases such as alcohols


⁵ Maximum of TWO (2) Electrochemical (EC) Sensors per unit

* Requires connection accessories, flexible tubes and connections available as option in the Si-AQ Kit Press. Diff.

All Si-AQ Pro Kits include:

- Temperature, %RH, Wet Bult, Dew Point
- Barometric Pressure
- PC Software & USB Cable
- Real-Time Continuous Data Logging
- Bluetooth® Connectivity
- Continuous Active Internal Sampling Pump
- Differential Pressure*
- Long Lasting Battery & AC Charger
- Factory Calibration Certificate
- Quick Start Guide


Optional Accessories



Bluetooth® Printer
(Si-AQ Bluetooth® Printer)



Sampling Probe
(Si-AQ Probe with Hose)



Moisture Exchange
Tube for Calibration
(Si-AQ Moisture Exchange)



Pitot Tube for Air Velocity
(Si-AQ Pitot Tube)