



DATA SHEET

SI 1805

Centrifugal pump

Sauermann® part # : SI1805SIUN23



Reduced dimensions

The SI 1805 pump is designed to be easily installed whatever the layout of the premises. Capable of evacuating up to 500 l/h, the SI 1805 pump is suitable for air conditioning units and industrial refrigeration displays.

Strong, the SI 1805 tolerates charged, high temperature and acidic condensates (pH > 3.4) produced by gas condensing boilers.

Benefits



High performance

- Can discharge condensates up to 5.4 m
- Up to 500 l/h, for shorter running time
- Low sound level – quiet operation



Easy hydraulic connection

- New quarter turn easily removable check valve, designed to facilitate Ø int. 10 mm (3/8") hose plug in.
- 2 inlet holes Ø 24 and 21 mm



Versatile

- Easily removable tank and reversible pump, to allow mounting rather on the left or on the right of the application and choosing the side of the water exit.



High resistance

- Oil and acid resistant float
- Mechanical structure resistant to shocks

Kit content

- One-piece centrifugal pump with tank (0.5 l)
- Integrated barb end check valve Ø ext. 10 mm (3/8")
- Power cable: (2 m with European plug)
- Safety switch cord: (1 m, bare ends)

Technical specifications

Max. flow rate	500 l/h
Max. discharge head	5.4 m
Max pressure	5.8 m (flowrate = 0)
Sound level in application at 1m (3.3 ft): ≤ 47 dBA (Measured in Sauermann acoustic lab, pump operating with water)	
Mains supply	230 V~ 50/60 Hz - 90 W
Detection levels	ON: 32 mm; OFF: 25 mm; Safety: 39 mm
Safety switch	NC 4 A resistive – 250V
Max. condensate temperature	65 °C, 80 °C in short peak
Max. condensate acidity	pH > 3.4 (Gas condensing boilers)
Thermal protection (overheating)	120 °C (auto-reset)
Operating conditions	30 %: 3 s ON – 7 s OFF
Protection	IP20
Safety standards	CE and EAC
RoHS directive	Compliant
WEEE directive	Compliant
Pump dimensions	L 195 x W 130 x H 132 mm
Tank dimensions	L 195 x W 130 x H 43 mm
Box dimensions	L 235 x W 135 x H 185 mm
Weight (including box)	2.0 kg
Packaging	10 pieces



Applications

- Column air conditioning units
- Multi cassettes
- Gas condensing boilers
- High efficiency gas furnace
- Refrigerated display cabinets
- Evaporators
- Ducted units

Accessories

Name	#Part
 Clear PVC tubing Ø int. 10 mm (3/8"), 25 m roll	ACC00911 ACC00915 (Braided)
 Float detector Used to operate an additional alarm or switch on the pump.	ACC00601
 Inlet adaptors Ø int. 24/25 mm Ø int. 32 mm Ø int. 40 mm	ACC00936 ACC00937 ACC00938
 Check valve For replacement Ø ext. 10 mm (3/8")	ACC00925

Actual flow rates (l/h)

Total tube length (Ø int. 10 mm, 3/8")

Vertical Discharge head	5 m	10 m	20 m	30 m
1 m	460	380	280	200
2 m	390	320	240	180
3 m	300	250	190	150
4 m	200	180	130	100
5 m	90	80	60	50